EM/TC Flipaway gate

2,500 lb., 3,300 lb. Capacities

Easy to Operate, Maintain, and Store, this Flipaway Gate Features Twin Cylinders for Maximum Clearance and Performance.

STANDARD EM SERIES ADVANTAGES INCLUDE:


- New wider and deeper platform sizes
 - Steel Platforms:
- Aluminum Platforms:
- 44" x 84" wedge
- 44" x 84" wedge
- 50" x 84" wedge
- 50" x 84" wedge
- Twin Cylinders require less mounting clearance and store higher up underneath truck for maximum ground clearance
- Twin cylinder hitch design works on lower bed height than single cylinder design (47" for single and 39" for twin)
- Bed extension with reinforced angle along entire width makes installation easier and reduces dishing
- 36" to 56" bed height range (Note: Larger 50" wedge platform fits 39" (laden) - 56" bed heights only)
- Grease fittings and maintenance free bearings at all major hinge points
- Easier installation with preset "A" dimension. Pump and cylinder installed and tested at factory
- Roll pins replaced with bolts to allow easier maintenance
- Snubber kit reduces potential liftgate wear caused by vibration during travel
- Powder coat finish with zinc primer on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

WALTCO

Designed Simplicity - Maximum Performance

Products shown may feature optional equipment Content subject to change without notice.

EM-25, EM-33 FULL DIP (WEDGE PLATFORM) BED LEVEL



Platform auto adjusts as it lowers from bed level to ground level



EM series gate in platform loading position. This liftgate is ideal for quick deliveries in tight spaces.

EM/TC LIPAWAY GATE



EM Series Gate in stowed position.



Bolt-on Parting Bar shown above.



Optional Steel Dock Bumper with Built-in Traction Step and Full **Coverage Rubber Pad**

SPECIFICATIONS:

Model	Capacity	Platform	Ramp
EMW/TC-25	2,500 lbs.	44" x 84"	Wedge
EMW/TC-25	2,500 lbs.	50" x 84"	Wedge
EMW/TC-33	3,300 lbs.	44" x 84"	Wedge
EMW/TC-33	3,300 lbs.	50" x 84"	Wedge
AP (Aluminum Platform)			
EMW/TC/AP-25	2,500 lbs.	44" x 84"	Wedge
EMW/TC/AP-25	2,500 lbs.	50" x 84"	Wedge
EMW/TC/AP-33	3,300 lbs.	44" x 84"	Wedge
EMW/TC/AP-33	3,300 lbs.	50" x 84"	Wedge

Notes: "EMW" denotes full-dip wedge style platform models

The 50" wedge has a minimum bed height of 39" laden

OPTIONAL EQUIPMENT:

- Hand-Held Pendant Control allows driver to operate the truck from the ground or bed level
- Remote Pump Mounting Kit offers the flexibility to install the pump unit • independently from the liftgate mount assembly when mounting space is an issue (recommended for low bed height mounting applications)
- Underride option available •
- Power-Down Operation for consistent performance regardless of weather . conditions or temperature (dual solenoid)
- Cab Shut-Off Switch allows operator to shut off power to control switches, preventing unauthorized use of the liftgate
- Dual Controls for street-side or curbside operation for added driver convenience
- Single or Two Step Steel Dock Bumpers with factory installed bumper block and bolt on capability protect the liftgate from damage caused by backing into loading docks
- Receiver-style hitch (Class IV 10,000 lb. rating with 1,000 lb. tounge weight) adds trailer towing versatility to vehicles with E Series liftgates (Draw bar and ball hitch not included; minimum 47" bed height on cylinder; 39" to 56" bed height with twin cylinder)
- Draw Bar Kit (Class III) gives 13" ball height range flexibility (ball hitch not included)
- Optional dual cart stops
- Galvanized option .
- **Customized Options contact factory** .

Waltco Lift Corp. Corporate Office United States United States 285 Northeast Ave.

Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418

Waltco Lift Corp.

620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149

Waltco Lift Inc. Canada 265 Export Blvd. Mississauga, ON L5S 1Y4 P: 888.343.4550

