



RGL SERIES

HEAVY DUTY RAIL GATE

2,000 lb., 3,000 lb., 4,000 lb.,
5,000 lb., and 6,600 lb. Capacities

**Large, Level-Ride,
Low-Profile Platforms**



STANDARD RGL SERIES ADVANTAGES INCLUDE:

- Power up / gravity down hydraulic system
- Platform opens and closes hydraulically with no cam mechanisms to wear or become misaligned
- Frame rail constructed of rugged 3/8" steel
- Rigid steel linkage on sides of 2-piece platform provides greater load stability
- External slide bearing simplifies maintenance and eliminates hard to access internal rollers
- Coated galvanized cable assemblies
- All wiring and connections meet or exceed all TMC recommended practices

OTHER STANDARD FEATURES:

- Weather-protective power unit enclosure
- Reduced Maintenance™ features including: self-lubricating, fiberglass-reinforced bearings at key pivot points
- Charge line circuit protection
- 12" Fixed Ramp standard on most 2-piece platform models
- Super Duty Motor
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

SLIMLINE LEVEL RIDE (Standard)



Platform remains level from vehicle bed to the ground.

Increase productivity with simplified handling of bulky, wheeled and palletized loads.



RGL Series Gate in stowed position

Products shown may feature optional equipment.
Content subject to change without notice.

WALTCO



SPECIFICATIONS

Bed Ht: 36"- 60" for (non-dock loading)
Bed Ht: 46"- 60" for dock loading)

MODEL	CAPACITY	PLATFORM	RAMP
RGL-20	2,000 lbs.	36" x 90"	6"
RGL-20	2,000 lbs.	42" x 90"	6"
RGL-20	2,000 lbs.	48" x 90"	16"
RGL-30	3,000 lbs.	36" x 90"	6"
RGL-30	3,000 lbs.	42" x 90"	6"
RGL-30	3,000 lbs.	48" x 90"	16"
RGL-30	3,000 lbs.	60" x 90"	12"
RGL-30	3,000 lbs.	72" x 90"	12"
RGL-40	4,000 lbs.	42" x 90"	6"
RGL-40	4,000 lbs.	48" x 90"	16"
RGL-40	4,000 lbs.	60" x 90"	12"
RGL-40	4,000 lbs.	72" x 90"	12"
RGL-50 †	5,000 lbs.	60" x 90"	12"
RGL-50 †	5,000 lbs.	72" x 90"	12"
RGL-50 †	5,000 lbs.	84" x 90"	16"
RGL-60 †	6,000 lbs.	60" x 90"	12"
RGL-60 †	6,000 lbs.	72" x 90"	12"
RGL-60 †	6,000 lbs.	84" x 90"	16"

Note: 42"- 48" deep platforms require a minimum 52" bed height for dock loading

† Requires Rail Extension Kit

OPTIONAL EQUIPMENT:

- 102" Wide Vehicle Option (increases steel platform widths to 96")
- Foot-Activated Cart Stops (available only on models with 12" fixed ramps)
- 16" Aluminum Retention Ramp with 90° lock reduces ground-to-platform incline and acts as a load retention device
- Auxiliary Pump & Motor Unit with Pendant Control: Industry's only backup power system complete with secondary control switches
- Bottom Stops allow operator to lower the folded platform into a pre-set dock loading position
- (†) Rail Extension Kit required for RGL-50, RGL-60 on bed heights greater than 53"
- Auxiliary Battery Power Kits for either straight truck or trailer applications
- Cycle Counter
- Customized Options – contact factory